

120 Watt, AQF120E Series, Enclosed Power Supply

ALL PSU LTD
Electronic Power Solutions

- Universal AC Input
- Fully Enclosed with options of U-Channel or Open Frame formats.
- High Efficiency Up To 92%
- Short Circuit, Over Voltage, Over Load Protected
- Convection Cooled To Full Power
- Full Approvals: UL/CE
- Compact Case Size



Specification

Input Voltage.....	90~264 VAC, 47~63 Hz (120-370 VDC)
Inrush Current.....	30 A @ 115 VAC, 60 A @ 230 VAC
Output Voltage.....	Single Outputs, See table below
Load Regulation.....	+/-1%
Line Regulation.....	+/-1%
Over Voltage Protection.....	Latch Off
Short Circuit Protection.....	Latch Off
Overload Protection.....	Auto Recovery
Hold Up Time.....	20 ms, min
Ripple & Noise.....	1% max
Input to Output Isolation.....	I/P-O/P: 4 kVAC,
Operating Temperature	-10 to +70 °C, see derating curve
Storage Temperature.....	-25 to +85 °C
Switching Frequency.....	100 kHz
Safety Standards.....	UL60950, CE
EMC.....	EN55022 class B, EN55024
Mechanical	127 x 82.2 x 38.1 mm
Connections Input & Output.....	Screw Terminals


Models and Ratings

Model	Output Voltage	Output Current	Efficiency
AQF120E-12S	12.0 V	10 A	90 %
AQF120E-24S	24.0 V	5 A	91 %
AQF120E-48S	48.0 V	2.5 A	92 %

Please see next page for mechanical drawings.



ALL PSU Ltd, Unit D6 Laser Quay, Culpeper Close, Medway City Estate,
Rochester, Kent, ME2 4HU, Tel : 01634 725527, Fax : 01634 739111
Email : sales@allpsu.co.uk, Web : www.allpsu.co.uk

Mechanical Drawings.



Connections	
Terminal	Function
1	AC Live
2	AC Neutral
3	Input Earth
4	+DC Out
5	+DC Out
6	-DC Out
7	-DC Out

Derating, (Input AC Supply & Temperature)



Specifications may change without notice. E&OE. ALL PSU Terms & Conditions apply.

**ALL PSU Ltd, Unit D6 Laser Quay, Culpeper Close, Medway City Estate,
Rochester, Kent, ME2 4HU, Tel : 01634 725527, Fax : 01634 739111,
Email : sales@allpsu.co.uk Web : www.allpsu.co.uk**