
## ALL PSU DATA SHEET.

## 60 Watt DE / DEL Open Frame Series, (Single Output, Small Footprint).

- \* Small 2 x4" Footprint
- \* Universal AC Input
- \* Low 1U Profile (open / cased)
- \* Cost Effective
- \* Short Circuit & Over Voltage
- Protection
- \* Class B Input Filter
- \* Optional Safety Covers
- \* Custom Versions Available



**Specification.** (@ 230 VAC Input, Rated Load, +25\*C)

Universal Input 90~264 VAC, 47~440-Hz (125-370 VDC)
Output Voltage See Table Below (plus min +/-5% adjustment)
(+10% Adjustment Available On 3.3 / 5 Volt Units)

Output Power Depends On Output Voltage / Cooling

Line Regulation (100~230 VAC) +/-0.2% Load Regulation (10~100%) +/-0.5%

Hold Up Time 16 mS (120 V Input @ 40 Watts Load) 50 mS (180 V Input @ 48 Watts Load)

50 mS (180 V Input @ 48 Watts Load) Over Voltage Protection Set To + 20% Above Nominal Output

Short Circuit Protection Continuous

Ripple And Noise Typically 1% (DC to 20MHz)

Switching Frequency 70 KHz

EMI Filter EN55022 For Conducted Noise

Isolation 4 KV Input To Output

Operating Temperature -10 To +70\*C (Derates 1.5%/\*C from 25 to 70\*C)

Storage Temperature -20 To +85\*C

Approvals UL & EN60950, CE Marked For LVD

Mechanical (open frame) Size 101.6 x 50.8 x 28mm (26mm from base of

PCB to top of highest heat-sink)

Connections Molex, 3.96mm pitch.

Optional Safety Cover Approximately 103 x 59 x 36mm

Model	Model	Output Voltage	<b>Convection Cooled</b>
RoHS Versions	Non RoHS		<b>Current Rating</b>
DE-60-3.3	DEL-60-101	3.3 Volts	8.0 Amps
DE-60-5	DEL-60-102	5.0 Volts	8.0 Amps
DE-60-12	DEL-60-103	12 Volts	5.0 Amps
DE-60-13.8	DEL-60-13.8	13.8 Volts	4.3 Amps
DE-60-15	DEL-60-15	15 Volts	4.0 Amps
DE-60-24	DEL-60-104	24 Volts	2.5 Amps
DE-60-48	DEL-60-105	48 Volts	1.25 Amps
Special, Dual & Triple Output Versions Available, Please Enquire.			

For full specification and mechanical details please contact ALL PSU sales office. Specifications may change without notice, E&OE. ALL PSU Terms & Conditions Apply.

Further Open Frame Units Are Available from 5 to 150 Watts. Please Visit <a href="https://www.allpsu.co.uk">www.allpsu.co.uk</a> For Further Product Listings.

ALL PSU Ltd, Unit D6 Laser Quay, Culpeper Close, Medway City Estate, Rochester, Kent, ME2 4HU, Tel: 01634 725527, Fax: 01634 739111 Email: sales@allpsu.co.uk, Web: www.allpsu.co.uk