

ALL PSU DATA SHEET.

60 Watt Desk Top, 1050 Series, (12 or 24 Volts Single Output).

- Universal Input
- 3 Pole IEC Inlet with Earth
- Full Approvals
UL/CUL/TUV/CE/CB
- 100% Burn In & Tested
- Protected For Short Circuit /
Over Load / Over Voltage.
- LED Power Indicator
- 1 Year warranty
- Low Cost / From Stock



Specification.

Input Voltage	90~264 Volts AC
Input Frequency	47~63 Hz
Efficiency	Typically 82%
Output Versions	12 Volts DC at 5 Amps 24 Volts DC at 2.5 Amps
Ripple & Noise	Typically 1%
Output Protection	Over Load, Short Circuit & Over Voltage.
Temperature Range	Operating -0* to +40*C Storage -20*C to +85*C
CE Marks	Compliance to Low Voltage & EMC Directives
Safety Standards	EN60950, UL, CUL, CE, TUV, CB, PSE, FCC, NORDIC, BSMI, EK, 3C
EMI Standards	EN60065, UL, CUL, TUV, CB, 3C
Input Connector	FCC Class B, EN55022 Class B
Output Connector	3 pin IEC inlet (IEC 320-C14) Standard 2.1mm Positive Centre Bore Options Of Other Alternatives Available.
Output Lead Length	Typically 1800 mm Minimum
Case Size	120mm x 60mm x 34mm.
AC Mains Lead	Also Available From ALL PSU Ltd. UK, Euro, USA etc...

Model	Output Voltage	Output Current	Ripple & Noise
EA-1050-A-120	12 V	5.0 A	120 mV
EA-1050-B-240	24V	2.5 A	150 mV

*Other Desktop Style Units Are Available From 10 to 120 Watts
 A Full List Of Standard Units Can Be found At www.allpsu.co.uk
 UK, Euro & USA Mains Leads Suitable For The Above Units Are Available From Stock.*

For full specification and mechanical drawing please contact ALL PSU sales office.
 Specifications are subject to change without notice, E&OE. ALL PSU Terms & Conditions Apply.

ALL PSU Ltd, Unit D6 Laser Quay, Culpeper Close, Medway City Estate,
 Rochester, Kent, ME2 4HU, Tel : 01634 725527, Fax : 01634 739111
 Email : sales@allpsu.co.uk, Web : www.allpsu.co.uk