

## ALL PSU DATA SHEET.

### 25 Watt Desk Top, P25A Series (Triple Output)

- Universal Input
- 3 Pole IEC Inlet with Earth
- Full Approvals  
UL/CUL/TUV/CE/CB
- 5 Pin DIN Output Connector
- 100% Burn In & Tested
- Protected For Short Circuit /  
Over Load / Voltage / Temp.
- Wide Temperature Range
- LED Power Indicator
- 1 Year warranty



#### Specification.

Input Voltage  
Inrush Current

90~264 VAC, 47~63 Hz  
Full Load/Cold Start, Peak  
<60 A @ 230 VAC, Max Values.


Output Voltage  
Ripple & Noise (p-p)  
Overload Protection  
Over Voltage Protection  
Operating Temperature  
Withstand Voltage

See Table Below  
See Table  
Hiccup Mode, Auto Recovery.  
110-140% for 5 Volts O/P.  
0~30°C @ Full Load, Derates to 70% @ 40°C  
I/P-O/P : 3KVAC,  
I/P-FG : 1.5KVAC for 1 Minute  
UL1950, TUV EN60950 Approved  
EN55022 Class B, EN61000-4-2,3,4,5,6,11  
EN61000-3-2,3

Safety Standards  
EMC Standards

Output Lead  
Output Plug DIN 5 Pin

150cm Typical



Model	Output	Tolerance	Ripple & Noise
P25A13D-R1B	+5V / 0.5~2.5A	+/-5%	50 mV
	+12V / 0.1~0.8A	+/-5%	100mV
	-12V / 0.1~0.3A	+/-3%	100mV
P25A14E-R1B	+5V / 0.5~2.5A	+/-5%	50 mV
	+15V / 0.1~0.5A	+/-5%	100mV
	-15V / 0.1~0.3A	+/-3%	100mV

*Other Desktop Style Units Are Available From 10 to 120 Watts.  
Please See Details On Our Web Site At [www.allpsu.co.uk](http://www.allpsu.co.uk)*

*UK, Euro & USA Mains Leads Suitable For The Above Units Are Available From Stock.*

For full specification and mechanical drawing please contact ALL PSU sales office.  
Specifications are subject to change without notice, E&OE. ALL PSU Terms & Conditions Apply.

ALL PSU Ltd, Unit D6 Laser Quay, Culpeper Close, Medway City Estate,  
Rochester, Kent, ME2 4HU, Tel : 01634 725527, Fax : 01634 739111  
Email : [sales@allpsu.co.uk](mailto:sales@allpsu.co.uk), Web : [www.allpsu.co.uk](http://www.allpsu.co.uk)