

ALL PSU DATA SHEET.

150 Watt Triple Output, (TP-150 Series).

- Universal Input With PFC
- High Efficiency/High Reliability
- Voltage Adjustment on O/P 1
- Short Circuit/Over Voltage/Over Load (Over Temp Protection- option)
- 100% Full Load Burn In Test
- Approvals UL/CUL/TUV/CB/CE
- 3 Years Warranty
- Built In DC Fan



Specification.

Input Voltage	90~264 VAC, 47~63Hz, 127~370 VDC
Power Factor	0.98 @ 115 VAC, 0.95 @ 230 VAC
Output Voltages	See Table Below, Adjust -5~+10%
Over Load Protection	105~150% O/P1, Auto Recovery
Set Up, Rise, Hold Up Time	800ms, 50ms, 16ms @ Full Load
Withstand Voltage	I/P-O/P:3KVAC, I/P-FG:1.5KVAC, 1Minute
Operating Temperature	-10~+60°C (Refer To Derating Curve)
Efficiency	75~78% Depending On Model
Safety Standards	UL 1950, TUV EN60950
EMC Standards	EN55022 Class B, EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11, ENV50204
Dimensions	199 x 99 x 50mm (plus screw terminals)

Model	Output 1	Output 2	Output 3	Max Power
TP-150A	+5V / 2~20A	+12V / 0.4~7A	-5V / 0~1A	150 W
TP-150B	+5V / 2~20A	+12V / 0.4~7A	-12V / 0~1A	148 W
TP-150C	+5V / 2~20A	+15V / 0.4~6A	-15V / 0~1A	151 W
TP-150D	+5V / 2~20A	+24V / 0.4~4A	+12V/0~1A	154 W

100 Watt Triple & Quad Output & 150 Watt Quad Output Versions Are Also Available.

For full specification and mechanical drawing please contact ALL PSU sales office.
Specifications can change without notice, E&OE.

*Further Single Or Multi Output Enclosed Units Can Be Seen At
www.allpsu.co.uk*

ALL PSU Ltd, Unit D6 Laser Quay, Culpeper Close, Medway City Estate,
Rochester, Kent, ME2 4HU, Tel : 01634 725527, Fax : 01634 739111
Email : sales@allpsu.co.uk, Web : www.allpsu.co.uk