

ALL PSU DATA SHEET.

40 Watt T Series. (Triple Output).

- Universal Input
- High Efficiency/Reliability
- 100% Full Load Burn In
- Short Circuit, Over Load, Over Voltage Protection
- Full Approvals : EN/UL/CSA/CE
- 2 Year Warranty
- Compact size, light weight
- Convection Cooled.



Specification

Input Voltage	85~264 VAC, 47~63Hz, 120~370 VDC
Inrush current	Cold Start, 20A/ 115, 40A/ 230V
Output Voltage	See Table Below (Output 1 +10%,-5%)
Over Load Protection	105~150% Output pulsing mode Auto Recovery
Over Voltage Protection	O/P1, 115~135% Of Output Voltage
Setup, Rise, Hold up time	800ms, 50ms, 60ms Full Load / 230VAC
Withstand Voltage	I/P-O/P : 3KV, I/P-FG:1.5KV, 1Min
Operating Temperature	0-50°C @ 100%, -10°C @ 80%, 60°C @ 60%
Safety Standards	CSA950, UL1950, IEC950, EN60950
EMC Standard	EN55022 class B, EN61000-3-2,3, EN61000-4-2,3,4,5

*DIN Rail Mounting Accessories Are Available For This Series.
Higher Power Single And Multi Output Units Are Also Available.*

Model	Output 1	Output 2	Output 3	Efficiency
T-40A	5V/0.6~5A	12V/0.2~3A	-5V/0.1~1A	72%
T-40B	5V/0.6~5A	12V/0.2~3A	-12V/0.1~1A	76%
T-40C	5V/0.6~5A	15V/0.2~2A	-15V/0.1~1A	76%

Units will operate safely with no minimum load but regulation specification may be slightly effected.

For full specification and mechanical drawing, please contact ALL PSU sales office.
Specifications can change without notice, E&OE

Further Single & Multi Output Units Can Be Seen At www.allpsu.co.uk

ALL PSU Ltd, Unit D6 Laser Quay, Culpeper Close, Medway City Estate,
Rochester, Kent, ME2 4HU, Tel : 01634 725527, Fax : 01634 739111,
Email : sales@allpsu.co.uk, Web : www.allpsu.co.uk