



electronic power solutions

EC4BW SERIES

10 WATT 4:1 INPUT RANGE

DC-DC CONVERTERS



FEATURES

- * 10W Isolated Output
- * 2"x1" Six-Sided Shield Metal Case
- * Efficiency to 82%
- * 4:1 Input Range
- * Pi Input Filter
- * Continuous Short Circuit Protection
- * Meets EN55022 Class A, Conducted



MODEL NUMBER	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT	INPUT CURRENT		% EFF.	CAPACITOR LOAD MAX.
				NO LOAD	FULL LOAD		
EC4BW01	9-36 VDC	5 VDC	2000 mA	15 mA	534 mA	78	2000uF
EC4BW02	9-36 VDC	12 VDC	830 mA	15 mA	520 mA	80	830uF
EC4BW03	9-36 VDC	15 VDC	666 mA	15 mA	520 mA	80	666uF
EC4BW04	9-36 VDC	±12 VDC	±415 mA	20 mA	520 mA	80	T.B.D.
EC4BW05	9-36 VDC	±15 VDC	±333 mA	20 mA	520 mA	80	T.B.D.
EC4BW06	9-36 VDC	±5 VDC	±1000 mA	20 mA	520 mA	80	T.B.D.
EC4BW07	9-36 VDC	3.3 VDC	2000 mA	15 mA	362 mA	76	2000uF
EC4BW11	18-72 VDC	5 VDC	2000 mA	10 mA	260 mA	80	2000uF
EC4BW12	18-72 VDC	12 VDC	830 mA	10 mA	257 mA	81	830uF
EC4BW13	18-72 VDC	15 VDC	666 mA	10 mA	257 mA	81	666uF
EC4BW14	18-72 VDC	±12 VDC	±415 mA	15 mA	257 mA	81	T.B.D.
EC4BW15	18-72 VDC	±15 VDC	±333 mA	15 mA	253 mA	82	T.B.D.
EC4BW16	18-72 VDC	±5 VDC	±1000 mA	15 mA	253 mA	82	T.B.D.
EC4BW17	18-72 VDC	3.3 VDC	2000 mA	10 mA	181 mA	76	2000uF

NOTE: 1. Nominal Input Voltage 24 or 48VDC

SPECIFICATIONS

All Specifications Typical At Nominal Line, Full Load, and 25°C Unless Otherwise Noted

INPUT SPECIFICATIONS:

Input Voltage Range	24V	9-36V
	48V	18-72V
Input Surge Voltage (100ms max.)	24V	50Vdc max.
	48V	100Vdc max.
Input Filter	Pi Type	

OUTPUT SPECIFICATIONS:

Voltage Accuracy	$\pm 1.0\%$ max.
Voltage Balance Dual Output at Full Load	$\pm 1.0\%$ max.
Transient Response	
Single 25% Step Load Change	<500us
Dual FL-1/2L $\pm 1\%$ Error Band	<500us
Ripple and Noise, 20MHz BW	75mV pk-pk max.
Temperature Coefficient	$\pm 0.02\%/{^\circ}\text{C}$ max.
Short Circuit Protection	Continuous
Line Regulation (note1).....	$\pm 0.2\%$ max.
Load Regulation (note2)	$\pm 1.0\%$ max.
Start up time	24Vin
	5ms typ.
	48Vin
	10ms typ.


NOTE:

1. Measured from high line to low line.
 2. Measured from full load to 1/4 load.
 3. Maximum case temperature under any operating condition should not be exceeded 100°C.

GENERAL SPECIFICATIONS:

Efficiency	See Table
Isolation Voltage	500 VDC
Isolation Resistance	10 ⁹ ohm min.
Isolation Capacitance	500pF typ.
Switching Frequency	300KHz typ.
Operating Ambient Temperature Range	-25°C to +71°C
De-rating, Above 71 °C	Linearly to Zero power at 100 °C
Case Temperature (note3)	100°C max.
Cooling	Natural Convection
Storage Temperature Range	-40°C to +100°C
Humidity	95% RH max. Non condensing
MTBF	MIL-STD-217F, GB, 25°C, Full Load 750K hrs Typ.
EMI/RFI	Six sided Continuous Shield
Dimensions	2.00x1.00x0.40 inches (50.8x25.4x10.2 mm)
Case Material	Black Coated Copper with Non-Conductive Base
Weight	32g

Typical Derating curve for Natural Convection




Case B Dimensions:

NOTE: Pin Size is 0.04 ± 0.004 Inch (1.0 ± 0.1 mm) DIA

All Dimensions In Inches (mm)

Tolerances Inches: X.XX= ± 0.04 , X.XXX= ± 0.010
 Millimeters: X.X= ± 1.0 , X.XXX= ± 0.25

Millimeters: X.X = ± 1.0 , X.XX = ± 0.25



**ALL PSU Ltd, Unit D6 Laser Quay, Culpeper Close, Medway City Estate,
Rochester, Kent, ME2 4HU, Tel : 01634 725527, Fax : 01634 739111
Email : sales@allpsu.co.uk, Web : www.allpsu.co.uk**