



MD-3W Series

3W 2:1 Regulated Single & Dual output

Features

- Wide 2:1 Input Range
- Full SMD Technology
- 1500VDC Isolation, Up to 3000VDC
- Continuous Short Circuit Protection
- Efficiency up to 81%
- -40°C ~ 85°C Operation Temperature Range
- EMC filter meets EN55032 Class A without adding external components
- Non-conductive Black Plastic DIL24-pin case



The MD series is a family of cost effective 3W single & dual output DC-DC converters. These converters combine Plastic case in a 24-pin DIL package with high performance features such as 1500VDC ~ 3000VDC input/output isolation voltage, continuous short circuit protection with automatic restart and high line / load regulation. Devices are encapsulated using flame retardant resin. Input voltages are 12Vdc, 24Vdc and 48Vdc with output voltages of 3.3, 5, 12, 15, 24, ±3.3, ±5, ±12, ±15 and ±24 Vdc. Featuring high efficiency operation up to 81% and output voltage accuracy of ±2% maximum. Also, no additional components adding required to comply with EN55032 Class A.

All specifications typical at Ta=25°C, nominal input voltage and full load unless otherwise specified.

OUTPUT SPECIFICATIONS	
Output Voltage Accuracy	±2%, max.
Output Voltage Blance (Dual Output)	±2%, max.
Output Current	See table, max.
Line Regulation	±0.5%, max.
Load Regulation (0% to 100%)	±1.2%, max.
Cross Regulation (Dual Output) (1)	±5%, max.
Ripple&Noise (20MHz Bandwidth) (2)	80mVpk-pk, max. Dual Output 24V:100mVpk-pk, max.
Over Load Protection	160% of Iout, typ.
Short Circuit Protection	Indefinite(hiccup) (Automatic Recovery)
Temperature Coefficient	±0.02%/°C
Capacitive Load (3)	See table
Transient Recovery Time (4)	300µs, typ.
Transient Response Deviation (4)	±3%, max. Single Output 3.3V:±5%, max.

INPUT SPECIFICATIONS	
Input Voltage Range	See table
Under Voltage Lockout	
12 Models Module ON / OFF	8.5Vdc / 7.0Vdc, typ.
24 Models Module ON / OFF	16.5Vdc / 14.5Vdc, typ.
48 Models Module ON / OFF	34.5Vdc / 30.0Vdc, typ.
Start up Time (Nominal Vin and constant resistive load)	20mS, typ.
Input Filter	Pi Type
Input Current (No-Load)	See table, max.
Input Current (Full-Load)	See table, typ.
Input Reflected Ripple Current (5)	20mApk-pk, typ.



EMC SPECIFICATIONS		
Radiated Emissions	EN55032	CLASS A
Conducted Emissions	EN55032	CLASS A
ESD	IEC 61000-4-2	Perf. Criteria A
RS	IEC 61000-4-3	Perf. Criteria A
EFT	IEC 61000-4-4	Perf. Criteria A
Surge(6)	IEC 61000-4-5	Perf. Criteria A
CS	IEC 61000-4-6	Perf. Criteria A
PFMF	IEC 61000-4-8	Perf. Criteria A

GENERAL SPECIFICATIONS	
Efficiency	See table, typ.
I/O Isolation Voltage(60sec) Input/Output	1500~3000Vdc
I/O Isolation Capacitance	1000pF, typ.
I/O Isolation Resistance	1000MΩ, min.
Switching Frequency	330kHz, typ.
Humidity	95% rel H
Reliability Calculated MTBF(MIL-HDBK-217 F)	>800 Khrs
Safety Approvals	UL/cUL 60950-1 , 62368-1 IEC/EN 60950-1 , 62368-1

PHYSICAL SPECIFICATIONS	
Case Material	Non-conductive Black Plastic(UL94V-0 rated)
Base Material	Non-conductive Black Plastic(UL94V-0 rated)
Pin Material	Φ0.5mm Brass Solder-coated
Potting Material	Epoxy (UL94V-0 rated)
Weight	13.0g
Dimensions	1.25"x0.8"x0.4"

ENVIRONMENT SPECIFICATIONS	
Operating Temperature	-40°C~85°C(See Derating Curve) -40°C ~ +70°C (For 100% load)
Maximum Case Temperature	100°C
Storage Temperature	-55°C~125°C
Cooling	Nature Convection

ABSOLUTE MAXIMUM RATINGS (7)	
These are stress ratings. Exposure of devices to any of these conditions may adversely affect long-term reliability.	
Input Surge Voltage (100mS)	
12 Models	25Vdc, max.
24 Models	50Vdc, max.
48 Models	100Vdc, max.
Soldering Temperature (1.5mm from case 10sec max.)	260°C, max.

MD - 3W 2:1 Regulated Single & Dual output
PART NUMBER STRUCTURE

MODEL SELECTION GUIDE

MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @FL (% , typ.)	Capacitor Load @FL (µF, max.)
		No-Load (mA, max.)	Full Load (mA, typ.)		Min. Load (mA)	Full Load (mA)		
MD-123R3S3	9-18	7	339	3.3	0	900	74	470
MD-1205S3	9-18	7	325	5	0	600	78	470
MD-1212S3	9-18	10	313	12	0	250	81	100
MD-1215S3	9-18	10	313	15	0	200	81	100
MD-1224S3	9-18	20	316	24	0	125	80	47
MD-123R3D3	9-18	10	339	±3.3	0	±450	74	±220
MD-1205D3	9-18	10	325	±5	0	±300	78	±220
MD-1212D3	9-18	15	313	±12	0	±125	81	±100
MD-1215D3	9-18	20	313	±15	0	±100	81	±100
MD-1224D3	9-18	35	319	±24	0	±63	80	±47
MD-243R3S3	18-36	7	172	3.3	0	900	73	470
MD-2405S3	18-36	7	164	5	0	600	77	470
MD-2412S3	18-36	7	156	12	0	250	81	100
MD-2415S3	18-36	7	156	15	0	200	81	100
MD-2424S3	18-36	10	156	24	0	125	81	47
MD-243R3D3	18-36	7	167	±3.3	0	±450	75	±220
MD-2405D3	18-36	7	160	±5	0	±300	79	±220
MD-2412D3	18-36	10	156	±12	0	±125	81	±100
MD-2415D3	18-36	15	156	±15	0	±100	81	±100
MD-2424D3	18-36	20	158	±24	0	±63	81	±47
MD-483R3S3	36-75	7	84	3.3	0	900	75	470
MD-48 05S3	36-75	7	80	5	0	600	79	470
MD-48 12S3	36-75	7	78	12	0	250	81	100
MD-48 15S3	36-75	7	78	15	0	200	81	100
MD-4824S3	36-75	7	78	24	0	125	81	47
MD-483R3D3	36-75	7	81	±3.3	0	±450	77	±220
MD-48 05D3	36-75	7	78	±5	0	±300	81	±220
MD-48 12D3	36-75	7	78	±12	0	±125	81	±100
MD-48 15D3	36-75	7	78	±15	0	±100	81	±100
MD-4824D3	36-75	15	81	±24	0	±63	79	±47


Suffix "H" means 3000Vdc isolation

NOTE



1. One load is 25% to 100% load, the other load is 100% load, the output voltage variable rate is within $\pm 5\%$.
2. Ripple/Noise measured with a $1\mu\text{F}$ ceramic capacitor.
3. Tested by minimal V_{in} and constant resistive load.
4. Tested by normal V_{in} and 25% load step change (75%-50%-25% of I_o).
5. Measured Input reflected ripple current with a simulated source inductance of $12\mu\text{H}$ and a source capacitor $C_{in}(47\mu\text{F}, \text{ESR}<1.0\Omega \text{ at } 100\text{KHz})$.
6. An external filter capacitor is required if the module has to meet IEC61000-4-5. The filter capacitor suggest: Nippon chemi-con KY series, $220\mu\text{F}/100\text{V}$.
7. Exceeding the absolute ratings of the unit could cause damage. It is not allowed for continuous operating.

TEST CONFIGURATIONS
Output Ripple & Noise Measurement Test

Use a capacitor $C_{out}(1.0\mu\text{F})$ measurement.
The Scope measurement bandwidth is 0-20MHz.


Input Reflected Ripple Current Test Step

Input reflected ripple current is measured through a source inductor $L_{in}(12\mu\text{H})$ and a source capacitor $C_{in}(47\mu\text{F}, \text{ESR}<1.0\Omega \text{ at } 100\text{KHz})$ at nominal input and full load.


MECHANICAL SPECIFICATIONS

**24 Pin DIL Package
Non-Conductive Plastic**

- Notes: All dimensions are typical in millimeters (inches).
1. Pin diameter: 0.5 ± 0.05 (0.02 ± 0.002)
 2. Pin pitch and length tolerance: ± 0.35 (± 0.014)
 3. Case Tolerance: ± 0.5 (± 0.02)

PIN CONNECTIONS

PIN NUMBER	SINGLE	DUAL
2	-V Input	-V Input
3	-V Input	-V Input
9	N.P.	Common
11	N.C.	-V Output
14	+V Output	+V Output
16	-V Output	Common
22	+V Input	+V Input
23	+V Input	+V Input

(The Pin Connection of high isolation one is the same with normal one.)

ALL PSU LTD, Unit D6 Laser Quay, Culpeper Close
Medway City Estate, Rochester, Kent, ME2 4HU

Tel: 01634 725527, Email: sales@allpsu.co.uk, Web: www.allpsu.co.uk

DRAWING:

APPROVED:

Last Update : 26.AUG.2020